


Клеммы тип *U* изолированные



Наименование	Габаритные размеры, мм						Сечение провода, мм ²	Сечение провода, AWG	Максимальный ток, А
	d2	B	L	F	H	D			
SV 1.25-3.2	3.2	5.7	21.2	6.5	10	4.3	0.5...1.5	22-16	19
SV 1.25-3.7L	3.7	6.4	21.2	6.5					
SV 1.25-3.7S	3.7	5.7	21.2	6.5					
SV 1.25-4L	4.3	8.1	21.2	6.5					
SV 1.25-4M	4.3	7.2	21.2	6.5					
SV 1.25-4S	4.3	6.4	21.2	6.5					
SV 1.25-5L	5.3	9.5	21.2	6.5					
SV 1.25-5S	5.3	8.1	21.2	6.5					
SV 2-3.2	3.2	5.7	21.2	6.5					
SV 2-3.7L	3.7	6	21.2	6.5					
SV 2-3.7S	3.7	5.7	21.2	6.5					
SV 2-4L	4.3	8.1	21.2	6.5					
SV 2-4M	4.3	7.2	21.2	6.5					
SV 2-4S	4.3	6.4	21.2	6.5					
SV 2-5L	5.3	9.5	21.2	6.5					
SV 2-5S	5.3	8.1	21.2	6.5					
SV 3.5-4	4.3	8	24.8	7.7	12.5	6.2	2.5...4	14-12	37
SV 3.5-5	5.3	8	24.8	7.7					
SV 3.5-6	6.5	12	28	12.1					
SV 5.5-3.7	3.7	8.3	25.2	7.5	12.5	6.7	4...6	12-10	48
SV 5.5-4L	4.3	9	23.9	7.5					
SV 5.5-4S	4.3	8.3	25.2	7.5					
SV 5.5-5	5.3	9	23.9	7.5					
SV 5.5-6L	6.5	12	31.2	12					